



DRIZORO S.A.U.

C/ Primavera, 50-52 - Parque Industrial Las Monjas - 28850 TORREJON DE ARDOZ - MADRID (SPAIN)
Tel. (34) 91 676 66 76 - 91 677 61 75 - Fax: (34) 91 675 78 13
INTERNET: www.drizoro.com - E-mail: info@drizoro.com

DECLARATION OF PERFORMANCE No. 327.00



1. Name and code of the product:

Product: MAXELASTIC PUR-E

Batch: See packaging

2. Name and contact address of the manufacturer or importer or distributor:

Name: DRIZORO, SAU

Contact address: C/Primavera 50-52. P. Ind. Las Monjas. 28850-Torrejón de Ardoz. (Madrid, Spain)

3. Intended use:

POLYURETHANE COATING FOR SURFACE PROTECTION OF CONCRETE.

PROTECTION AGAINST INGRESS, AND MOISTURE CONTROL.

4. System of assessment and verification of constancy of performance: System 2+

5. Notified body:

Name and identification number: AENOR, 0099

Notified task: Assessment of the Factory Production Control

System of assessment: System 2+

Certificate of the Factory Production Control: 0099/CPR/B15/0010

6. Declared performance

Essential Characteristics	Performance	Harmonised Technical Specification
PERMEABILITY TO CO ₂	S _D > 50 m	EN 1504-2:2004
WATER VAPOUR PERMEABILITY	Class II: 5m <S _D <50m	EN 1504-2:2004
CAPILLARY ABSORPTION AND PERMEABILITY TO WATER	< 0,1 kg.m ⁻² .h ^{-0.5}	EN 1504-2:2004
ADHESION	≥ 1,0 N/mm ²	EN 1504-2:2004
REACTION TO FIRE	NPD	EN 1504-2:2004
DANGEROUS SUBSTANCES	COMPLY 5.3	EN 1504-2:2004

- The performance of the product identified in point 1 is in conformity with the declared performance in point 6.
- This declaration of performance is issued under the sole responsibility of the manufacturer, importer or distributor identified in point 2.
- Signed for and behalf of the manufacturer, or importer or distributor by:

(Signature)
 DRIZORO, S.A.U.
 C/ Primavera, 50 - 52
 Parque Industrial Las Monjas
 Tel. (34) 91 676 66 76 - 91 677 61 75
 TORREJON DE ARDOZ (Madrid)

Mr. Francisco Rodríguez Álvarez
Director of Quality and Environment.

Torrejón de Ardoz, 1st July, 2013



Empresa certificada ISO 9001 - ISO 14001
N° 663176 - 663176-MA

