(in accordance with Regulation (EU) 2015/830)

MAXFIX-P

 Version: 1
 Page 1 of 9

 Revision date: 12/11/2016
 Print date: 21/01/2017

DRIZOR

Construction Products



1.1 Product identifier.

Product Name: MAXFIX-P

1.2 Relevant identified uses of the mixture and uses advised against.

Chemical anchorage for the construction

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: DRIZORO, S.A.U.

Address: C/ Primavera, 50 - 52 Parque Industrial Las Monjas

City: 28850 Torrejón de Ardoz

 Province:
 Madrid (Spain)

 Telephone:
 +34 91 676 66 76

 Fax:
 +34 91 675 11 31

 E-mail:
 info@drizoro.com

1.4 Emergency telephone number: +34 91 676 66 76 (Only available during office hours)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the mixture.

In accordance with Regulation (EU) No 1272/2008:

Acute Tox. 4: Harmful if inhaled.

Eye Irrit. 2 : Causes serious eye irritation. Skin Irrit. 2 : Causes skin irritation.

Skin Sens. ${\bf 1}$: May cause an allergic skin reaction.

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:



Signal Word:

Warning

H statements:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H332 Harmful if inhaled.

P statements:

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P501 ispose of contents / container in accordance with local legislation in force

P302+P352 IF ON SKIN: Wash with plenty of water/...

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

(in accordance with Regulation (EU) 2015/830)

MAXFIX-P

Version: 1

Page 2 of 9 **Revision date: 12/11/2016** Print date: 21/01/2017

DRIZOR

Construction Products

easy to do. Continue rinsing.

Contains:

dibenzoyl peroxide, benzoyl peroxide

2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
Identifiers			Classification	specific concentration limit
Index No: 601-026- 00-0 CAS No: 100-42-5 EC No: 202-851-5 Registration No: 01- 2119457861-32-XXXX	[1] styrene	12.5 - 25 %	Acute Tox. 4 *, H332 - Eye Irrit. 2, H319 - Flam. Liq. 3, H226 - Repr. 2, H361d - STOT RE 1, H372(órganos de audición) - Skin Irrit. 2, H315	-
Index No: 617-008- 00-0 CAS No: 94-36-0 EC No: 202-327-6 Registration No: 01- 2119511472-50-XXXX	[1] dibenzoyl peroxide, benzoyl peroxide	0 - 2.5 %	Eye Irrit. 2, H319 - Org. Perox. B, H241 - Skin Sens. 1, H317	-

^(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

SECTION 4: FIRST AID MEASURES.

IRRITANT PREPARATION. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

If wearing contact lenses, remove them. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

Skin contact.

See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

^[1] Substance with a Community workplace exposure limit (see section 8.1).

(in accordance with Regulation (EU) 2015/830)

MAXFIX-P

Version: 1

Revision date: 12/11/2016



Page 3 of 9 Print date: 21/01/2017

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. **NEVER** use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. **NEVER** induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate. Can cause allergic reactions.

Harmful Product, prolonged exposure due to inhalation may cause anaesthetic effects and the need for immediate medical assistance.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

SECTION 5: FIREFIGHTING MEASURES.

The product does not present any particular risk in case of fire.

5.1 Extinguishing media.

Recommended extinguishing methods.

Extinguisher powder or CO_2 . In case of more serious fires, also alcohol-resistant foam and water spray. Do not use a direct stream of water to extinguish.

5.2 Special hazards arising from the mixture.

Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and gloves.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

The contaminated area should be immediately cleaned with an appropriate de-contaminator. Pour the decontaminator on the remains in an opened container and let it act various days until no further reaction is produced.

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

For personal protection, see section 8. Never use pressure to empty the containers. They are not pressure-resistant containers.

(in accordance with Regulation (EU) 2015/830)

MAXFIX-P

 Version: 1
 Page 4 of 9

 Revision date: 12/11/2016
 Print date: 21/01/2017

DRIZOR

Construction Products

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 35° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

Not available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m³
ch rene	100-42-5	United	Eight hours	100	430
styrene	100-42-3	Kingdom [1]	Short term	250	1080
dibenesal perevide benesal perevide	xide 94-36-0	United	Eight hours		5
dibenzoyl peroxide, benzoyl peroxide		Kingdom [1]	Short term		

[1] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adobted by Health and Safety Executive. The product does NOT contain substances with Biological Limit Values. Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Туре	Value
styrene	DNEL	Inhalation, Long-term, Systemic effects	85
N. CAS: 100-42-5	(Workers)		(mg/m³)
N. CE: 202-851-5			
dibenzoyl peroxide, benzoyl peroxide	DNEL	Inhalation, Long-term, Systemic effects	11,75
N. CAS: 94-36-0	(Workers)		(mg/m ³)
N. CE: 202-327-6			,

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %
Uses:	Chemical anchorage for the construction
Breathing protect	ion:
PPE:	Particle filter mask
Characteristics:	«CE» marking, category III. Made of filtering material, it covers nose, mouth and chin.
CEN standards:	EN 149
Maintenance:	Check for any tears, defects, etc. before use. Since it is disposable individual protection equipment, it should be replaced after use.
Observations:	Does not protect worker unless properly adjusted. Follow the manufacturer's instructions regarding suitable use of the equipment.
Filter Type needed:	P2
Hand protection:	
PPE:	Protective gloves against chemicals.
Characteristics:	«CE» marking, category III.

(in accordance with Regulation (EU) 2015/830)

MAXFIX-P

Version: 1 Page 5 of 9 Revision date: 12/11/2016 Print date: 21/01/2017

DRIZOR

Construction Products

EN 374-1, En 374-2, EN 374-3, EN 420 CFN standards:

Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Maintenance:

Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or

Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Observations:

Always use with clean, dry hands.

Breakthrough time Material thickness Material: PVC (polyvinyl chloride) > 480 0,35 (min.): (mm):

Eye protection: PPE: Protective goggles against particle impacts.

Characteristics: «CE» marking, category II. Eye protector against dust and smoke.

CEN standards: EN 165, EN 166, EN 167, EN 168

Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should Maintenance:

be disinfected periodically following the manufacturer's instructions.

Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, Observations:

scraping etc.

Skin protection:

PPE: Anti-static protective clothing.

«CE» marking, category II. Protective clothing should not be too tight or loose in Characteristics:

order not to obstruct the user's movements.

CFN standards: EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5

In order to guarantee uniform protection, follow the washing and maintenance instructions provided by Maintenance:

the manufacturer.

The protective clothing should offer a level of comfort in line with the level of protection provided in

Observations: terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level

of activity and the expected time of use.

PPE: Anti-static safety footwear. Characteristics: «CE» marking, category II.

EN ISO 13287, EN ISO 20344, EN ISO 20346 CEN standards:

The footwear should be checked regularly Maintenance:

The level of comfort during use and acceptability are factors that are assessed very differently depending Observations:

on the user. Therefore, it is advisable to try on different footwear models and, if possible, different

widths.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Appearance: Paste with characteristic colour and odour

Colour: N.A./N.A. Odour: N.A./N.A.

Odour threshold: N.A./N.A.

pH:N.A./N.A.

Melting point: N.A./N.A. Boiling Point: 142,5 °C Flash point: 33 °C

Evaporation rate: N.A./N.A.

Inflammability (solid, gas): N.A./N.A. Lower Explosive Limit: N.A./N.A. Upper Explosive Limit: N.A./N.A. Vapour pressure: N.A./N.A. Vapour density: N.A./N.A.

Relative density: Comp.A: 1.7, Comp.B: 1.6 g/cm³

Solubility: N.A./N.A. Liposolubility: N.A./N.A. Hydrosolubility: N.A./N.A.

Partition coefficient (n-octanol/water): N.A./N.A.

Auto-ignition temperature: N.A./N.A. Decomposition temperature: N.A./N.A.

Viscosity: N.A./N.A.

Explosive properties: N.A./N.A.

-Continued on next page.-

(in accordance with Regulation (EU) 2015/830)

MAXFIX-P

Version: 1

Revision date: 12/11/2016



Page 6 of 9 Print date: 21/01/2017

Oxidizing properties: N.A./N.A. N.A./N.A. N.A./N.A.= Not Available/Not Applicable due to the nature of the product

9.2 Other information. Pour point: N.A./N.A. Blink: N.A./N.A.

Kinematic viscosity: N.A./N.A.

N.A./N.A.= Not Available/Not Applicable due to the nature of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Unstable in contact with:

- Acids.
- Bases.
- Oxidizing agents.

10.3 Possibility of hazardous reactions.

In certain conditions this may cause a polymerization reaction.

10.4 Conditions to avoid.

Avoid the following conditions:

- Heating.
- High temperature.
- Contact with incompatible materials.

10.5 Incompatible materials.

Avoid the following materials:

- Acids.
- Bases
- Oxidizing agents.

10.6 Hazardous decomposition products.

Depending on conditions of use, can be generated the following products:

- COx (carbon oxides).
- Organic compounds.
- Aromatics compounds.

SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT PREPARATION. Splatters in the eyes can cause irritation.

IRRITANT PREPARATION. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

11.1 Information on toxicological effects.

There are no tested data available on the product.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Splatters in the eyes can cause irritation and reversible damage.

a) acute toxicity;

Product classified:

Acute toxicity (Inhalation), Category 4: Harmful if inhaled.

b) skin corrosion/irritation;

Product classified:

Skin irritant, Category 2: Causes skin irritation.

c) serious eye damage/irritation;

Product classified:

(in accordance with Regulation (EU) 2015/830)

MAXFIX-P

Version: 1

Page 7 of 9 **Revision date: 12/11/2016** Print date: 21/01/2017

DRIZOR

Construction Products

Eye irritation, Category 2: Causes serious eye irritation.

d) respiratory or skin sensitisation;

Product classified:

Skin sensitiser, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Based on available data, the classification criteria are not met.

h) STOT-single exposure;

Not conclusive data for classification.

i) STOT-repeated exposure;

Based on available data, the classification criteria are not met.

j) aspiration hazard;

Not conclusive data for classification.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

No information is available regarding the ecotoxicity of the substances present.

12.2 Persistence and degradability.

No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potencial.

Information about the bioaccumulation of the substances present.

Name		Bioaccumulation			
		Log Pow	BCF	NOECs	Level
styrene		3,05	_	_	Moderate
N. CAS: 100-42-5	EC No: 202-851-5	3,03	_	-	Moderate

12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13 DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

(in accordance with Regulation (EU) 2015/830)

MAXFIX-P

Version: 1

Revision date: 12/11/2016



Page 8 of 9 Print date: 21/01/2017

SECTION 14: TRANSPORT INFORMATION.

Transportation is not dangerous. In case of road accident causing the product's spillage, proceed in accordance with point 6.

14.1 UN number.

Transportation is not dangerous.

14.2 UN proper shipping name.

Description:

ADR: Transportation is not dangerous. IMDG: Transportation is not dangerous. ICAO: Transportation is not dangerous.

14.3 Transport hazard class(es).

Transportation is not dangerous.

14.4 Packing group.

Transportation is not dangerous.

14.5 Environmental hazards.

Transportation is not dangerous.

14.6 Special precautions for user.

Transportation is not dangerous.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

Transportation is not dangerous.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Volatile organic compound (VOC)

VOC content (p/p): 14,3 % VOC content: 234 g/l

The product is not affected by Directive 2012/18/EU (SEVESO III).

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

15.2 Chemical safety assessment.

H332

There has been no evaluation a chemical safety assessment of the product.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H226	Flammable liquid and vapour.
H241	Heating may cause a fire or explosion.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

Harmful if inhaled.

(in accordance with Regulation (EU) 2015/830)

MAXFIX-P

Version: 1

Revision date: 12/11/2016



Page 9 of 9 Print date: 21/01/2017

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.(órganosdeaudición)

Classification codes:

Acute Tox. 4 [Inhalation]: Acute toxicity (Inhalation), Category 4

Eye Irrit. 2 : Eye irritation, Category 2 Flam. Liq. 3 : Flammable liquid, Category 3 Org. Perox. B : Organic peroxide, Type B Repr. 2 : Reproductive toxicant, Category 2

STOT RE 1 : Specific target organ toxicity following a repeated exposure, Category 1

Skin Irrit. 2 : Skin irritant, Category 2 Skin Sens. 1 : Skin sensitiser, Category 1

Sections changed compared with the previous version:

1,2,3,8,9,10,16

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used: BCF: Bioconcentration factor.

CEN: European Committee for Standardization.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be

considered a tolerable minimum.

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not

anticipated.

EC50: Half maximal effective concentration. PPE: Personal protection equipment. LC50: Lethal concentration, 50%.

LD50: Lethal dose, 50%.

Log Pow: Logarithm of the partition octanol-water. NOEC: No observed effect concentration.

Key literature references and sources for data:

http://eur-lex.europa.eu/homepage.html

http://echa.europa.eu/ Regulation (EU) 2015/830.

Regulation (EC) No 1907/2006.

Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a quarantee of its properties.